

**AMENDMENTS TO THE CLAIMS****Claims pending**

- At time of the Action: Claims 1-8, 10-20.
- After this Response: Claims 1-8, 10-20.

**Canceled or Withdrawn claims:** 9.

**Amended claims:** The previous cancellation of claim 9 is clarified, per 37 CFR § 1.121.

**New claims:** None.

Please amend the claims as indicated below:

1. (Previously Presented) A cable drop support system comprising:
  - a base adapted for attachment to a surface;
  - at least one segment connected to the base;
  - a cable receptacle attached to a portion of the at least one segment, the cable receptacle being structured for receiving therein at least a portion of a cable;
  - a control system operatively associated with the cable drop support system, the control system configured for receiving instructions communicated through at least one communication media;
  - at least one mechanical drive mechanism operatively coupled to respond to the control system.
2. (Original) The cable drop support system of Claim 1, wherein the attachment surface includes a surface area portion of a service vehicle.
3. (Original) The cable drop support system of Claim 1, wherein the base includes at least one attachment device structured for attachment of the base to the attachment surface.
4. (Original) The cable drop support system of Claim 3, wherein the base is substantially permanently attached to the attachment surface.

5. (Original) The cable drop support system of Claim 3, wherein the base is removably attached to the attachment surface.
6. (Original) The cable drop support system of Claim 1, further comprising at least a second segment attached to the at least one segment.
7. (Original) The cable drop support system of Claim 6, further comprising the segments being structured in a telescoping configuration.
8. (Original) The cable drop support system of Claim 1, wherein the cable receptacle includes a generally upwardly open U-shaped configuration.
9. (Cancelled).
10. (Previously Presented) The cable drop support system of Claim 1, wherein the control system is selected from the group consisting of a computer system, a processor, and a manual control.
11. (Previously Presented) The cable drop support system of Claim 1, wherein the communication media includes at least one of a wireless medium and a wireline medium.
12. (Original) The cable drop support system of Claim 1, further comprising at least one control system operatively associated with the cable drop support system, the control system configured for receiving instructions communicated through at least one communication media from at least one communication device.

13. (Original) The cable drop support system of Claim 12, wherein the communication device is selected from the group consisting of a remote control device, a laptop, a personal digital assistant, and a telephone.

14. (Previously Presented) The cable drop support system of Claim 1, further comprising at least one remote control device operative over the communication media to cause the mechanical drive mechanism to extend the cable receptacle relative to the base.

15. (Original) The cable drop support system of Claim 14, further comprising at least a second segment attached to the at least one segment.

16. (Original) The cable drop support system of Claim 15, further comprising the first and second segments being structured in a telescoping configuration.

17. (Original) The cable drop support system of Claim 16, further comprising a hand crank operatively associated with the mechanical drive mechanism.

18. (Original) The cable drop support system of Claim 1, wherein the at least one segment includes a substantially stationary segment attached to the base.

19. (Previously Presented) A cable drop support system comprising:

a base adapted for attachment to a surface, wherein the attachment surface includes a surface portion area of a service vehicle;

a first segment connected to the base;

at least a second segment attached to the first segment, the first and second segments being structured in a telescoping configuration;

a cable receptacle attached to a portion of at least one of the segments, the cable receptacle being structured for receiving therein at least a portion of a cable, the cable receptacle including a generally upwardly open U-shaped configuration;

a control system operatively associated with the cable drop support system, the control system configured for receiving instructions communicated through at least one communication media;

at least one mechanical drive mechanism operatively coupled to respond to the control system.

20. (Previously Presented) A cable drop support system for facilitating installation of a cable between at least two elevated structures, with a portion of the cable being secured to a first one of the elevated structures and with a second portion of the cable to be secured to at least a second one of the elevated structures, the system comprising:

a base adapted for attachment to a surface, wherein the attachment surface includes a surface area portion of a service vehicle;

a first segment connected to the base;

at least a second segment attached to the first segment, the first and second segments being structured in a telescoping configuration to extend vertically away from the base;

a cable receptacle attached to a portion of at least one of the segments, the cable receptacle being structured for receiving therein at least a portion of the cable, the cable receptacle including a generally upwardly open U-shaped configuration;

at least one computer-based control system operatively associated with the cable drop support system, the control system configured for receiving instructions communicated through at least one wireless communication media from at least one communication device from a technician, wherein the communication device

is selected from the group consisting of a remote control device, a laptop, a personal digital assistant, and a telephone;

at least one mechanical drive mechanism operatively coupled to the control system and to the first and second segments to selectively extend the cable receptacle in response to the instructions, whereby when the second portion of the cable is placed in the cable receptacle and the cable receptacle is extended, the second portion of the cable is raised toward the second elevated structure to facilitate securing the second portion of the cable thereto; and

a battery coupled to provide power to the mechanical drive mechanism.